



Size		d	D	L	L ₁	H	OP	K	J	SPRING RETURN		DOUBLE ACTING	
DN	NPS									H ₁	L ₂	H ₁	L ₂
15	1½"	15	21.8	73	10	44.5	9	36	50	135	162	124	139.5
20	2"	20	27.5	80	13	46	9	36	50	153	207	136.5	162
25	1"	25	34.7	90	13	56.4	11	42	50	163.4	207	146.9	162
32	1¼"	32	43.0	110	16	70.3	11	42	50	177.3	207	160.8	162
40	1½"	38	49.5	120	16	79	14	50	70	197.5	237.5	186	207
50	2"	50	61.5	140	18	86.7	14	50	70	218.2	271.5	215.2	237.5
65	2½"	64	77.0	185	18	114	17	70	102	275.5	328	245.5	271.5
80	3"	74	90	205	20	121	17	70	102	294.5	366	282.5	328
100	4"	100	115.2	240	20	140	17	70	102	336	428	313.5	366



APPLICABLE STANDARDS & TECHNICAL NOTES:

TEST PRESSURE									
HYDROSTATIC		SHELL			SEAL				
		60 kg/cm ²			44 kg/cm ²				
AIR		/			/				
TITLE: BUTT WELDING BALL VALVE									
DN15-DN100									
					DWG NO: FT0114000003-1.1				
									
1	2006.2.1	ZhuHui	Brian	Sky Tang					
REV	Date	DRN	CHK	APRV	SCALE			UNIT	mm